


# EASY WALL

## dispositivo di telecontrollo GSM

### GSM remote control device

TL.033.000



**Conforme alle direttive**  
**Compliance to:**  
 2006/95/CE Low voltage  
 2004/108/CE Electromagnetic Compatibility  
 1999/5/CE R&TTE

**Norme di riferimento**  
**Reference standards:**  
 EN60950-1:2006  
 EN60730-1:2011  
 EN61000-4-2:2011  
 EN61000-4-3:2006  
 EN 301 489-1 ver.1.9.2:2011-09  
 EN 301 489-7 ver.1.3.1:2005-11  
 EN 301 511 ver. 9.02:2003-03

Alimentazione	12Vdc (min 9Vdc, max 14Vdc)
Assorbimento	3.5W Max
Frequenza	850 - 900 - 1800 -1900 MHz Quad Band
Tipo antenna	Stilo avvitabile SMA M
n°2 ingressi digitali	Configurabili N.O. / N.C.
n°1 sonda interna	NTC 10K @25°C ±1%
n°1 sonda esterna	NTC 10K @25°C ±1% (opzionale)
n°2 uscite relé	2 x 3A @ 400 Vac
n°1 connettore USB	micro USB (tipo B) (presente a seconda della versione hardware)
Lunghezza fili sonda esterna	3m max, oppure fino a 25 m con cavo schermato
Risoluzione temperatura	0.1°C
Isteresi allarmi temperatura	2.0 °C (per 60 sec)
Campo di misura sonda interna	0.0 .. 105.0 °C
Campo di misura sonda esterna	-35.0 .. 105.0 °C
Campo di misura	-20.0 .. 55.0 °C
Batterie tampone	3xAAA NiMh 1,2V 800..1000 mAh
Temperatura funzionamento	-20 .. +55.0 °C
Temperatura stoccaggio	-20 .. +55.0 °C
Limiti umidità	20 .. 80 % RH non condensante
Grado di protezione	IP30
Contenitore - Materiale	ABS V0 autoestinguente
Colore	RAL 9003 (Bianco segnale)
Peso	~ 98 gr
Dimensioni	75x25x75 mm
Installazione	Montaggio a parete

Power Supply	12Vdc (min 9Vdc, max 14Vdc)
Absorption	3.5W Max
Frequency	850 - 900 - 1800 -1900 MHz Quad Band
Antenna type	Stylus Antenna SMA M
n°2 digital inputs	Configurable N.O. / N.C.
n°1 internal probe	NTC 10K @25°C ±1%
n°1 external probe	NTC 10K @25°C ±1% (optional)
n°2 output relays	2 x 3A @ 400 Vac
n°1 USB connector	micro USB (type B) (present depending on the hardware version)
Length wires external probe	3m max, or up to 25 m with shielded cable
Temperature resolution	0.1°C
Temperature alarms hysteresis	2.0 °C (for 60 sec)
Measuring range internal probe	0.0 .. 105.0 °C
Measuring range external probe	-35.0 .. 105.0 °C
Measuring range	-20.0 .. 55.0 °C
Backup batteries	3xAAA NiMh 1,2V 800..1000 mAh
Operating temperature	-20 .. +55.0 °C
Storage temperature	-20 .. +55.0 °C
Humidity limits	20 .. 80 % RH non-condensing
Protection	IP30
Case - Material	ABS V0 self-extinguishing
Color	RAL 9003 (Signal white)
Weight	~ 98 gr
Dimensions	75x25x75 mm
Installation	Wall Mount